

R1

Date of printing 03/08/2023

Technical data

NOTE: The photo shows a general example of the product.

Peso de la máquina, máx.	1500 - 3500 kg
Anchura de la cuchara, máx.	1000 mm
Fuerza de arranque, máx.	35 kN
Par de arranque, máx.	25 kNm
[WeightFrom]	90 kg
[TiltAngle]	40°
Velocidad de rotación (1 revolución por)	7,0 s at 15 l/min
[WorkingPreassure]	21 MPa
Presión de la línea de retorno, máx.	2,0 MPa at 25 l/min
Caudal hidráulico, mín.	21 l/min
Número de puntos de lubricación	5
[TurnTorque]	1650 Nm at 21 MPa
[TiltTorqueB]	5800 Nm



Measurement specification

Dimensión A, anchura	Dimensión B, altura de instalación total	Dimensión C, longitud	Dimensión D, altura de instalación
290 mm	1150 mm	456 mm	333 mm

The products in the photos may have additional accessories and features.

Technical data and weights may vary depending on the configuration and equipment. We reserve the right to change specifications or designs without prior notice and assume no responsibility for any actual errors that may occur. There may be variations in product programs and equipment standards between the markets. For more information concerning current product specifications, local adaptations and special equipment, please contact your nearest sales office.

