

R2

Date of printing 03/08/2023

Technical data

NOTE: The photo shows a general example of the product.

| | |
|---|---------------------|
| Peso de la máquina, máx. | 3000 - 6500 kg |
| Anchura de la cuchara, máx. | 1200 mm |
| Fuerza de arranque, máx. | 50 kN |
| Par de arranque, máx. | 43 kNm |
| [WeightFrom] | 175 kg |
| [TiltAngle] | 40° |
| Velocidad de rotación (1 revolución por) | 7,0 s at 30 l/min |
| [WorkingPreassure] | 25 MPa |
| Presión de la línea de retorno, máx. | 2,0 MPa at 40 l/min |
| Caudal hidráulico, mín. | 42 l/min |
| Número de puntos de lubricación | 3 |
| [TurnTorque] | 3900 Nm at 25 MPa |
| [TiltTorqueB] | 14400 Nm |



Measurement specification

| Dimensión A, anchura | Dimensión B, altura de instalación total | Dimensión C, longitud | Dimensión D, altura de instalación |
|----------------------|--|-----------------------|------------------------------------|
| 314 mm | 810 mm | 468 mm | 389 mm |

The products in the photos may have additional accessories and features.

Technical data and weights may vary depending on the configuration and equipment. We reserve the right to change specifications or designs without prior notice and assume no responsibility for any actual errors that may occur. There may be variations in product programs and equipment standards between the markets. For more information concerning current product specifications, local adaptations and special equipment, please contact your nearest sales office.

