

# R3

Date of printing 03/08/2023

## Technical data

NOTE: The photo shows a general example of the product.

<b>Peso de la máquina, máx.</b>	6000 - 12000 kg
<b>Anchura de la cuchara, máx.</b>	1500 mm
<b>Fuerza de arranque, máx.</b>	81 kN
<b>Par de arranque, máx.</b>	85 kNm
<b>[WeightFrom]</b>	300 kg
<b>[TiltAngle]</b>	40°
<b>Velocidad de rotación (1 revolución por)</b>	7,0 s at 50 l/min
<b>[WorkingPreassure]</b>	25 MPa
<b>Presión de la línea de retorno, máx.</b>	2,0 MPa at 70 l/min
<b>Caudal hidráulico, mín.</b>	69 l/min
<b>Número de puntos de lubricación</b>	6
<b>[TurnTorque]</b>	6100 Nm at 25 MPa
<b>[TiltTorqueA]</b>	21500 Nm
<b>[TiltTorqueB]</b>	26500 Nm



## Measurement specification

Dimensión A, anchura	Dimensión B, altura de instalación total	Dimensión C, longitud	Dimensión D, altura de instalación
677 mm	939 mm	607 mm	467 mm

The products in the photos may have additional accessories and features. Technical data and weights may vary depending on the configuration and equipment. We reserve the right to change specifications or designs without prior notice and assume no responsibility for any actual errors that may occur. There may be variations in product programs and equipment standards between the markets. For more information concerning current product specifications, local adaptations and special equipment, please contact your nearest sales office.

