

# R4

Date of printing 03/08/2023

## Technical data

NOTE: The photo shows a general example of the product.

<b>Peso de la máquina, máx.</b>	10000 - 16000 kg
<b>Anchura de la cuchara, máx.</b>	1600 mm
<b>Fuerza de arranque, máx.</b>	125 kN
<b>Par de arranque, máx.</b>	163 kNm
<b>[WeightFrom]</b>	380 kg
<b>[TiltAngle]</b>	40°
<b>Velocidad de rotación (1 revolución por)</b>	7,0 s at 60 l/min
<b>[WorkingPreassure]</b>	25 MPa
<b>Presión de la línea de retorno, máx.</b>	2,0 MPa at 95 l/min
<b>Caudal hidráulico, mín.</b>	91 l/min
<b>Número de puntos de lubricación</b>	6
<b>[TurnTorque]</b>	7640 Nm at 25 MPa
<b>[TiltTorqueA]</b>	26500 Nm
<b>[TiltTorqueB]</b>	38600 Nm



## Measurement specification

Dimensión A, anchura	Dimensión B, altura de instalación total	Dimensión C, longitud	Dimensión D, altura de instalación
729 mm	1037 mm	705 mm	503 mm

The products in the photos may have additional accessories and features.

Technical data and weights may vary depending on the configuration and equipment. We reserve the right to change specifications or designs without prior notice and assume no responsibility for any actual errors that may occur. There may be variations in product programs and equipment standards between the markets. For more information concerning current product specifications, local adaptations and special equipment, please contact your nearest sales office.

