

# RC5

Date of printing 03/08/2023

## Technical data

NOTE: The photo shows a general example of the product.

<b>Peso de la máquina, máx.</b>	14000 - 19000 kg
<b>Anchura de la cuchara, máx.</b>	1700 mm
<b>Fuerza de arranque, máx.</b>	140 kN
<b>Par de arranque, máx.</b>	200 kNm
<b>[TiltAngle]</b>	40°
<b>Velocidad de rotación (1 revolución por)</b>	7,0 s at 72 l/min
<b>[WorkingPressure]</b>	25 MPa
<b>Presión de la línea de retorno, máx.</b>	2,0 MPa at 100 l/min
<b>Caudal hidráulico, mín.</b>	121 l/min
<b>[TurnTorque]</b>	9550 Nm at 25 MPa
<b>[TiltTorqueB]</b>	56600 Nm



## Measurement specification

<b>Dimensión A, anchura</b>	<b>Dimensión B, altura de instalación total</b>	<b>Dimensión C, longitud</b>	<b>Dimensión D, altura de instalación</b>
819 mm	1228 mm	801 mm	601 mm

The products in the photos may have additional accessories and features.

Technical data and weights may vary depending on the configuration and equipment. We reserve the right to change specifications or designs without prior notice and assume no responsibility for any actual errors that may occur. There may be variations in product programs and equipment standards between the markets. For more information concerning current product specifications, local adaptations and special equipment, please contact your nearest sales office.

