

RC8

Date of printing 03/08/2023

Technical data

NOTE: The photo shows a general example of the product.

Peso de la máquina, máx.	23000 - 32000 kg
Anchura de la cuchara, máx.	2000 mm
Fuerza de arranque, máx.	200 kN
Par de arranque, máx.	330 kNm
[WeightFrom]	760 kg
[TiltAngle]	40°
Velocidad de rotación (1 revolución por)	8,0 s at 129 l/min
[WorkingPreassure]	25 MPa
Caudal hidráulico, mín.	134 l/min
Flujo hidráulico recomendado, mín.	134 l/min
Número de puntos de lubricación	5
[TurnTorque]	12 Nm at 25 MPa
[TiltTorqueB]	64700 Nm



Measurement specification

Dimensión A, anchura	Dimensión B, altura de instalación total	Dimensión C, longitud	Dimensión D, altura de instalación
950 mm	1333 mm	920 mm	673 mm

The products in the photos may have additional accessories and features.

Technical data and weights may vary depending on the configuration and equipment. We reserve the right to change specifications or designs without prior notice and assume no responsibility for any actual errors that may occur. There may be variations in product programs and equipment standards between the markets. For more information concerning current product specifications, local adaptations and special equipment, please contact your nearest sales office.

